


RC

HOLLOW-CONE NOZZLES

IN-LINE IMPACT



RC type nozzles produce a wide-angle hollow cone spray, in-line with the feed pipe. The spray is produced through impact, resulting in high efficiency.

Connection: Male thread

Materials: Brass (T1)
303 stainless steel (B1)

Nozzle code	RG	Flow rates (gpm) at various pressures (psi)									Dimensions	
		5	10	20	30	40	60	80	100	WS	H	
		150°	RCY 1780 xx SN	1/4"	0.70	1.0	1.4	1.7	2.0	2.4	2.8	3.1
	RCY 2117 xx SN		1.1	1.5	2.1	2.6	3.0	3.7	4.2	4.7		
	RCY 2157 xx SN		1.4	2.0	2.8	3.5	4.0	4.9	5.7	6.3		
	RCY 2196 xx SN		1.8	2.5	3.5	4.3	5.0	6.1	7.1	7.9		
	RCY 2230 xx SN	3/8"	2.1	2.9	4.2	5.1	5.9	7.2	8.3	9.3	7/8"	147/64"
	RCY 2270 xx SN		2.4	3.4	4.9	6.0	6.9	8.4	9.7	10.9		
	RCY 2310 xx SN		2.8	4.0	5.6	6.9	7.9	9.7	11.2	12.5		
	RCY 2350 xx SN		3.2	4.5	6.3	7.7	8.9	10.9	12.6	14.1		
	RCY 2390 xx SN		3.5	5.0	7.0	8.6	10.0	12.2	14.1	15.7		
180°	RCZ 1780 xx SN	1/4"	0.70	1.0	1.4	1.7	2.0	2.4	2.8	3.1	11/16"	119/64"
	RCZ 2117 xx SN		1.1	1.5	2.1	2.6	3.0	3.7	4.2	4.7		
	RCZ 2157 xx SN		1.4	2.0	2.8	3.5	4.0	4.9	5.7	6.3		
	RCZ 2196 xx SN		1.8	2.5	3.5	4.3	5.0	6.1	7.1	7.9		
	RCZ 2230 xx SN	3/8"	2.1	2.9	4.2	5.1	5.9	7.2	8.3	9.3	7/8"	147/64"
	RCZ 2270 xx SN		2.4	3.4	4.9	6.0	6.9	8.4	9.7	10.9		
	RCZ 2310 xx SN		2.8	4.0	5.6	6.9	7.9	9.7	11.2	12.5		
	RCZ 2350 xx SN		3.2	4.5	6.3	7.7	8.9	10.9	12.6	14.1		
	RCZ 2390 xx SN		3.5	5.0	7.0	8.6	10.0	12.2	14.1	15.7		

HYDRAULIC NOZZLES
HOLLOW-CONE